

DL-200 Thermal Label Printer



Tally
DASCOM

Tally Dascom's DL-200 thermal transfer printer offers reliability, precision and performance in desktop size.

The user friendly design of the printer allows a space saving vertical opening and an easy to use printer mechanism ensures quick media and ribbon loading. The clear panel enable simple and effective operation making it very simple to use.

Highlights at a glance:

- 5 inches / sec speed printing
- Easy ribbon and paper loading
- Small, compact footprint
- Supports a variety of interfaces
- Supports ZPL, EPL and TSC emulations
- Optional cutter, peeler, large paper roll support

The DL-200 is easily integrated into existing systems as it supports a wide variety of interfaces. In addition to this, the DL-200 is also available with an optional cutter or peeler to meet the various requirements.

Configurations:

- Standard Product (USB only)
- Printer with Parallel / Serial / WIFI / Ethernet / Bluetooth interface option
- Printer with cutter
- Printer with peeler
- Printer with large paper roll support

DL-200

| | |
|----------------------------|---|
| Print Speed | 5 ips (127 mm/sec) |
| Print Width | 4"/ 108 mm |
| Print Method | Direct Thermal or Thermal Transfer |
| Print Head Lifetime | 30 km or 6 months whichever is earlier |
| Resolution | 203 dpi |
| Fonts | Font A - Font V (ZPL) User defined fonts can be downloaded into FLASH/SDRAM |
| Memory | 8 MB SDRAM; 8 MB Flash |
| Interface | USB (2.0 Full Speed) |
| Interface Options | Serial (RS-232C), Parallel (IEEE-1284), Ethernet, WIFI, Bluetooth |
| Emulations | ZPL, EPL, TSC |
| Ribbon | Width: 30 - 110 mm; Length: 74 m Core diameter: 12.7 mm; Outside diameter: 35 mm |
| Media | Width: 25.4 - 120 mm; Thickness: 0.05 - 0.32 mm Core diameter: 25.4 / 38.1 mm; Outside diameter: 127 mm (Large Roll model: 160 mm) |
| Media Type | Thermal paper, media, black mark paper |
| Sensors | Paper detection sensor; Black mark sensor, Label gap sensor, Ribbon sensor, Mechanical sensor Optional: paper taken sensor |
| Barcode | 1D: Code 39, UPC-A, UPC-E, Matrix 25, Industrial 2 of 5, Interleaved 2 of 5, Post 2 of 5, Code 128, EAN-8, EAN-13, HBIC (Code 39), Codabar, UPC-2, UPC-5, Code 93 2D: PDF 417, MaxiCode, QR Code, Data MatrixR |
| Physical Weight | 1.85 kg |
| Physical Size | 173 x 207 x 241 mm (H x W x D) / Large Roll model: 208 x 207 x 278 (H x W x D) |
| Power Voltage | 100-240 V AC, 50-60Hz |
| Printer Driver | Windows (32/64 Bit) |
| Temperature | Operating: 5° C - 40° C |
| Humidity | Operating: 20% - 95% (not-condensing) |
| Acoustic | < 55 dB(A) |
| Options | Cutter, Peeler, Large Roll Model |

DASCOM AP Pte Ltd

21 Bukit Batok Crescent

#29-81 WCEGA Tower

Singapore 658065

Tel: +65 6760 8833 – Fax: +65 67601066

sales@dascom.com.sg – www.dascom.com.sg

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS