WorkForce Pro EM-C800RDWF



The WorkForce Pro EM-C800RDWF is a high ink-yield 4-in-1 with scan capability and up to 1,830 paper capacity.

The EM-C800RDWF RIPS inkjet printer offers a solution for efficient, uninterrupted, high-volume printing without changing supplies. With seamless integration (to third party solutions), small footprint and low Total Cost of Ownership (TCO), it's ideal for all businesses. Low power consumption¹, Fast First Page Out Time (FPOT)², 25 ppm print speed³ make this great for office environments.

High productivity, low intervention

A fast FPOT of 4.8 seconds from ready mode² and single-pass duplex scan increase productivity. Print up to 50,000 pages (mono) and 20,000 pages (colour) without changing supplies⁴. A paper capacity of up to 1,830 sheets (3 x optional 500 sheet cassettes) means less time spent refilling paper. Print speeds of 25ppm³ and 60 ipm duplex scan speed, make this an ideal sprinter for a wide range of industry sectors: from healthcare to education.

Heat-Free printing technology

Built with efficiency in mind, EM-C800RDWF offers low power consumption1. By switching to Heat-Free printing technology, which uses no heat in the ink ejection process, you can save energy, time and reduce intervention¹.

Low running costs

High ink-yields lower the need to order and replace supplies frequently⁴, help to deliver predictable print costs and a competitive TCO. Lower costs of servicing and intervention making this a reliable and attractive choice for businesses. Low power consumption delivers much needed savings¹.

Solutions that are built for business

With workflow and security, fleet management and remote services, Epson Solutions Suite has you covered. Easy remote diagnosis with Epson Remote Services, Epson Print Admin (EPA) to aid your print security requirements all boost additional functionality.

DATASHEET / BROCHURE























KEY FEATURES

- High productivity, low intervention 25 ppm print³, 60 ipm duplex scan speeds and Fast FPOT of 4.8 sec²
- Efficient compact A4 4-in-1
 10.9 cm colour touchscreen with fax and ADF Print, copy, scan & fax
- Save on costs
 Low TCO and save energy, with Epson's
 Heat-Free printing technology¹
- Built for business
 Compact with up to 50k mono ink-yield⁴
 and 1,830 max paper capacity
- Epson Solutions Suite
 Smooth system integration and freedom to work anywhere



TECHNOLOGY

Printing Method PrecisionCore™ Micro TFP printhead

Nozzle Configuration 800 Nozzles Black, 800 Nozzles per Color

Minimum Droplet Size 3.8 pl, With Variable-Sized Droplet Technology

Ink Technology DURABrite™ Ultra, Replaceable Ink Pack System (RIPS)

Category Office Workgroup

All-in-One Functions Print, Scan, Copy, Fax

PRINT

Number of colours 4 colour

First Page Out Monochrome4.8 Seconds, Colour5.3 Seconds
Printing Speed ISO/IEC 24734 25 pages/minMonochrome, 25 pages/minColour
Duplex Printing Speed 16 A4 Pages/minMonochrome, 16 A4 Pages/minColour

ISO/IEC 24734

Maximum Printing Speed 34 pages/minMonochrome (plain paper 75 g/m²), 34 pages/minColour (plain paper 75 g/m²)

Printing Resolution 4,800 x 1,200 DPI
Printing Volume 70,000 pages per month

The maximum number of printed pages per month based on the performance capabilities of

the printer, including ISO rated print speeds and paper handling capabilities.

Recommended Duty Cycle 500 - 5,000 pages per month

Colours Black, Cyan, Yellow, Magenta

Print from PC, MAC, Network, Mobile Device, USB, Cloud, PC (Wired), PC (Wireless), Mobile Device (WiFi

Direct)

For detailed information on printing speeds please visit http://www.epson.eu/testing.

SCAN

Scanning Speed 30 ipm (Monochrome, Single-sided, 200 dpi, ADF); 30 ipm (Colour, Simplex, 200 dpi, ADF);

60 ipm (Monochrome, Double-sided, 200 dpi, ADF); 60 ipm (Colour, Double-sided, 200 dpi, ADF); 5 sec/page (Monochrome, Single-sided, 200 dpi, Flatbed); 5 sec/page (Colour, Single-sided, 200 dpi, Single-sided, 200 dpi,

sided, 200 dpi, Flatbed);

Optical Resolution 1,200 DPI x 2,400 DPI (Horizontal x Vertical)
Optical Resolution (ADF) 1,200 DPI x 2,400 DPI (Horizontal x Vertical)

Advanced document Scan to Email, Scan to FTP, Scan to Network folders, Computer (Epson Document Capture

integration Pro), USB Memory Device / Card

Output formats JPEG, TIFF, multi-TIFF, PDF, PDF/A, JPEG(Colour/Greyscale)

Scanner type Contact image sensor (CIS)

Optical Resolution 1,200 DPI x 2,400 DPI (Horizontal x Vertical)

WorkForce Pro EM-C800RDWF

WHAT'S IN THE BOX

- Initialization Ink Supply Units
- Power cable
- Setup guide



WorkForce Pro EM-C800RDWF

FAX

Walk-up black and white and colour fax capability Type of fax

Fax Transmission Speed Up to 33.6kbps / Approx. 3 sec/page

Error correction mode CCITU/ITU Group3 fax with Error Correction Mode

Fax speed dials (max) 2.000 names and numbers

Page memory Up to 550 pages/ 6MB (ITU-T No. 1 chart)

Fax Functions PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Speed Dial, Fax to Folder, Address

Book, Broadcast Fax, Fax Preview

COPY

Copy Speed Up to22 ipm Black, Up to22 ipm Colour

*Simplex ADF 600 x 600 dpi (ISO/ IEC 24735)

Copy resolution (dpi) 600 x 1200 25 % - 400 % Reduction / Enlargement Maximum number of copies 999 Maximum Copy Size

CONNECTIVITY

Network Printing Protocols

Network Management Protocols

LPR, IPP, LDP, Port 9100, WSD, TCP/IPv6, IPSec, IPPS, Bonjour/Airprint, SMB 2.0, SMB 3.0 SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping, SMTP, TCP/IPv4, TCP/IPv6, IPSec, IEEE 802.1X, DCHP, HTTPS, LDAP, SNMP 2.0c, SNMP 3.0

Network Protocol HTTPS, IPv4, IPv6, SNMP

Network Scanning Protocols WSD-Scan, Bonjour/Airprint, FTP, SMB 2.0, SMB 3.0

Interfaces

Hi-Speed USB - compatible with USB 2.0 specification, Ethernet Interface (1000 Base-T/100-

Base TX/ 10-Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wi-Fi Direct

WLAN Security WEP 64 Bit, WEP 128 Bit, WPA2 Enterprise, WPA2 PSK (AES), WPA3-SAE(AES)

Network Protocol TCP/IPv4, TCP/IPv6, HTTP, HTTPS, IPv4, IPv6, IPSEC, SSL/TLS

PAPER / MEDIA HANDLING

Paper Formats A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B5, B6, C4 (Envelope), C6 (Envelope),

DL (Envelope), No. 10 (Envelope), Letter, Legal, 9×13 cm, 10×15 cm, 13×18 cm, 16:9, HLT,

EXE. User defined

Automatic Document Feed 50 pages Compatible Paper Weight 64 - 300g/m²

Yes

Standard Paper input 250 SheetsStandard, 80 SheetsMP tray

Output Tray Capacity 150 Sheets

330 SheetsStandard, 1,830 SheetsMaximum Paper Tray Capacity Standard paper tray(s) 80-Sheet Multi-Purpose Tray, 250-sheet paper tray

Optional paper tray(s) 3 x 500 sheet paper tray

Maximum paper input 1,830 Number of paper trays 2

PAPER FEED MPT

Paper Input Name

A4, A5, A6, B5, B6, C4 (Envelope), C6 (Envelope), DL (Envelope), No. 10 (Envelope), Letter, $10\,\mathrm{x}$ Paper Formats

15 cm, 13 x 18 cm, 16:9, Legal, Executive

Min64x 127 mm to Max215.9x 6.000 mm **Custom sizes**

Compatible paper weight 64g/m² - 300g/m²

80 Sheets of Plain Paper, Postcards, Glossy paper, Envelopes, 80gsm Paper Capacity 1

Paper Capacity 2 Sheets of Plain Paper, 80gsm

Media type Plain Paper, Recycled Paper, Colour Paper, Letterhead, Glossy Photo Paper



WorkForce Pro EM-C800RDWF

PAPER FEED C1

Paper Input Name (

Paper Formats A4, A5, A6, B5, B6, C4 (Envelope), C6 (Envelope), DL (Envelope), No. 10 (Envelope), Letter,

HLT. Executive

Custom sizes Min89x 127 mm to Max215.9x 355.6 mm

Compatible paper weight 64g/m² - 160g/m²

Paper Capacity 1 250 Sheets of Plain Paper, 80gsm

Media type Plain Paper, Recycled Paper, Colour Paper, Letterhead, Glossy Photo Paper

PAPER FEED C2

Paper Input Name C2

Paper Formats A4, A5, A6, B5, B6, Letter, HLT, Legal, Executive Custom sizes Min100x 148 mm to Max215.9x 355.6 mm

Compatible paper weight 64g/m² - 160g/m²

Paper Capacity 1 500 Sheets of Plain Paper, 80gsm

Media type Plain Paper, Recycled Paper, Colour Paper, Letterhead

PAPER FEED DUPLEX

Paper Input Name Duplex

Paper Formats A4, A5, A6, B5, B6, Letter, HLT, Legal, Executive

Custom sizes Min148x 210 mm to Max216x 297 mm

Compatible paper weight 64g/m² - 160g/m²

Media type Plain Paper, Recycled Paper, Colour Paper, Letterhead

GENERAL

Energy Use 30 Watt(standalone copying, ISO/IEC 24712 pattern), 1.1 Watt(sleep mode), 13.8 Watt(Ready),

0.2 Watt(Power off), TEC0.18 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz

Supply Voltage AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions 425 x 535 x 413 mm (Width x Depth x Height)

Product dimensions 425 x 535 x 413 mm (Width x Depth x Height

Product weight 21.3 kg

Compatible Operating Citrix XenApp 7.6 and above, Citrix XenDesktop Version 7.6, Linux, Mac OS 10.10.x, Mac OS Systems 10.14. x, Mac OS 10.15. x, Mac OS 11. x, Mac OS 12. x, Mac OS X 10.11.x, Mac OS X 10.11.x

or later, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.9.5 or later, SAP, Windows 10 (32/64 bit), Windows 11, Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022, Windows Vista (32/64 bit), Windows

XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit)

Included Software Epson Scan 2
Sound Power Operation:6.5 B (A)
Noise Operation:51 dB (A)

Mobile and Cloud printing Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Apple AirPrint,

services Mopria, Epson Smart Panel App

Power supply 220V, 240V

ADDITIONAL FEATURES

Memory 3,072 MB

Features Touchscreen, Direct Print, Direct print from USB
Panel Type: Color, Touchscreen, Diagonal:10.9 cm

Media Handling ADF 2-sided copy (A4, plain paper), Automatic duplex (A4, plain paper), Portrait & Landscape

printing, Thick Media Support

Security Functions Limit access function with Epson Web Config, Secure confidential printing with PIN code

release, LDAP Address Book, IPsec, IEEE802.1x, SSL (Server authentication), Panel Admin

Mode



WorkForce Pro EM-C800RDWF

PRODUCT SAFETY

Product Safety Warnings Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

 $Contains\ 2,4,7,9-tetramethyldec-5-yne-4,7-diol.\ May\ produce\ an\ allergic\ reaction.$

Always follow the information on the product label.

OTHER FEATURES

Emulations PCL5c, PCL6, ESC/P-R, PostScript 3, PDF 1.7

Security TLS, TLS V1.2, TLS V1.3, SSL, IEE 802, SNMP V3, IPSec, IPv6, HTTPs, WPA2, WPA3, PIN code

Release, LDAP, IEEE802, SSL/TLS, Panel Admin Mode

OTHER

Warranty 12 months On-site service

Optional warranty extension available



SUPPLIES

 WorkForce Pro EM/EP-C800R Black XXL Ink 	C13T11P140	50,000	()
 WorkForce Pro EM/EP-C800R Cyan XXL Ink 	C13T11P240	20,000	()
 WorkForce Pro EM/EP-C800R Magenta XXL Ink 	C13T11P340	20,000	()
 WorkForce Pro EM/EP-C800R Yellow XXL Ink 	C13T11P440	20,000	()
 WorkForce Pro EM/EP-C800R Black XL Ink 	C13T11N140	10,000	()
 WorkForce Pro EM/EP-C800R Cyan XL Ink 	C13T11N240	5,000	()
 WorkForce Pro EM/EP-C800R Magenta XL Ink 	C13T11N340	5,000	()
 WorkForce Pro EM/EP-C800R Yellow XL Ink 	C13T11N440	5,000	()

WorkForce Pro EM-C800RDWF

OPTIONAL ACCESSORIES

- 500-Sheet Paper Cassette Unit for 58xx/53xx C12C937901
- 58xx/53xx Series Maintenance Box C12C938211
- Paper Feed Roller for Cassette A (58XX/53XXSeries) C12C938261
- Paper Feed Roller for Cassette B (58XX/53XXSeries) C12C938281
- Authentication Device Table-P2 C12C939531

LOGISTICS INFORMATION

SKU	C11CK19401
EAN code	8715946715797
Country of Origin	Indonesia
Layer	2 Units

For further information please contact your local Epson office or visit www.epson-europe.com
Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09
74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway 6. +47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) in

465-9621 Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal – 0,99 kr/min, Lokala samtal – 0,30 kr/min, Utlandssamtal – 0,89 kr/min) Switzerland 022 592 7923

Turkey (0212) 3360303 United Kingdom 0871 222 6702

3. Time between receiving print data, to the complete exit of the first page. For detailed information on printing speeds please visit epson.eu

5. The productivity has been determined in accordance with ISO 24734, using default settings. The average of ESAT from the office category test. The full detailed report can be obtained from your local Epson sales office.

7. Approx. page yield. Actual yield will vary depending on images printed and usage conditions. For more information visit epson.eu/pageyield



^{*} Warranty offers are not available for all countries. Please contact your local Epson representative.

^{1.} Please visit epson.eu/heat-free-technology for more information.