

FCS-4042 Version: 1



! Mounting kits are to be ordered separately.

## PTZ Dome Outdoor Network Camera, 2-Megapixel, 802.3at PoE+, 30X Optical Zoom



1. Reset Button  
2. Power LED

3. Memory Card Slot  
4. Power Input

5. Ethernet Port  
6. Audio Input

7. Audio Output  
8. Digital Input/ Output

### Key Features

- 2-Megapixel (1920 x 1080) high-definition resolution
- 360° pan and 190° tilt movements allow for a wide range of monitoring angles
- Supports 30X optical zoom
- 
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Features 3DNR (3-Dimension Noise Reduction) to produce extremely clear picture quality even under low light condition
- 3D privacy masks for private area protection
- Removable IR-cut filter for day and night surveillance
- Built-in Micro SDHC/SDXC card slot for local storage
- Dual power support: 24VAC/PoE (IEEE 802.3af/at)
- Weatherproof IP67-rated housing
- Free video surveillance and CMS (Central Management System) software with 64-channel license

## Specifications

### System Specifications

#### Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet  
IEEE 802.3u 100-BASE-TX, Fast Ethernet  
IEEE 802.3af Power over Ethernet (PoE)  
IEEE 802.3at Power over Ethernet (PoE+)  
TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour

#### Image Sensor:

2-Megapixel 1/2.8" Progressive Scan CMOS

#### Connectors and Cabling:

1 x RJ-45 10/100 Mbps PoE plus port  
1 x Line In  
1 x Line Out  
1 x Power terminal block  
I/O terminal block (4 DI/2 DO)  
1 x MicroSDHC/ MicroSDXC card slot

#### Button/Knob:

Reset Button

#### Indicator:

Power

#### Lens:

Zoom, DC iris, Auto focus, f4.3-129mm, F1.6-5.0

#### IR Cut Filter:

Removable infrared-cut filter for day & night function

#### Shutter Time:

1/5 ~ 1/10,000 sec

#### Angle of View:

66.4° - 2.61°

#### Pan/Tilt/Zoom:

Pan range: 360°  
Tilt range: -20° ~ 200°  
30x Optical Zoom  
16x Digital Zoom  
Preset Point  
Auto pan mode  
Auto patrol mode

#### Video Compression:

H.264 / MJPEG

#### Resolution:

2M (1920x1080)

#### Video Format:

RAW

#### Audio Compression:

G.711

#### Power Input:

AC24V / 802.3at PoE

**Power Consumption:**

High PoE (IEEE802.3at) / 25.44 W (built-in heater and fan on), AC 24V / 31.5 W (built-in heater and fan on)

**Features****General:**

Backup: MicroSDHC /MicroSDXC card slot for local storage

**Security:**

Alarm and Notification: Alarm: Motion Detection; Tampering Detection; Network Failure Detection; DI/DO

Notification: HTTP, FTP, SMTP

Access Control: Multi-level user access with password protection

IP address filtering

IEEE 802.1X network access control

HTTPS encrypted data transmission

**Video:**

Image Setting: - Adjustable image size, quality and bit rate

- Configurable brightness, sharpness, contrast, saturation, white balance and exposure

- AGC/AWB/AES

- Back Light Compensation (BLC)

- Wide Dynamic Range (WDR), Extreme WDR (145dB)

- 3D Noise Reduction (3DNR)

- Flip & Mirror

- Portrait Mode

- Privacy Mask

- Time Stamp and Text Caption Overlay

Image Layout:

Streaming: Up to 4 video streams

Motion Detection: 10 Detection Zones

**Audio:**

Streaming: 2-way audio

Input/Output: line input, line output

**Performance****Data Transfer Rate:**

10/100Mbps

**Storage Capacity:**

SD/MicroSD memory card of up to 64GB

**Frame Rate:**

30 fps at 1920 x 1080; 30 fps at 1280 x 720; 30 fps at 640 x 480; 15 fps at 320 x 240

**Minimum illumination:**

Color: 0.1 lux at F1.6

B/W: 0.05 lux at F1.6

**Environment****Temperature (°C):**

Operating: -40°C ~ 50°C (AC 24V with heater and fan)

0°C ~ 40°C (PoE Plus, without heater and fan)

**Humidity (Non-condensing):**

Operating: 10% ~ 85%

**Deployment:**

Wall Mount

## Physical Specifications

Dimensions (W x D x H mm):

200 x 276 x 200 mm

Weight (g):

2500 g

## Approval and Compliance

EMI/EMS:

CE, RoHS, FCC, ONVIF, IP67, IK09, NEMA 4X

Environmental Test:

Weather proof IP67-rated housing


Vandal Resistant IK09-rated

## Others

Operation Systems:

Microsoft Windows 8/7/Vista/XP

## Diagram



## Order Information

FCS-4042

## Package Contents

FCS-4042

Power Adapter

Power Cord

Screw Kit

Quick Installation Guide

Resource CD (User Manual, QIG)

## Optional Accessory



**CAS-2101**  
Pendant Cap



**CAS-2102**  
Pendant Mount Bracket



**CAS-2103**  
Pendant Mount Bracket



**CAS-2104**  
Extension Tube



**CAS-2402**  
Corner mount



**CAS-2503**  
Pole Mount for PTZ, hemispheric and dome cameras



**CAS-2702**  
Outdoor Junction Box



**CAS-4312**  
Wall Mount Bracket, Cable Management



No liability or responsibility for any errors or omissions in the content.  
Specifications are subject to change without notice.  
All mentioned brand names are registered trademarks and property of their owners.  
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.