

# Onvie



FCS-3054 Version: 1

# Fixed Dome Network Camera, 3-Megapixel, 802.3af PoE, Vandalproof



## **Key Features**

- Built-in Micro SDHC/SDXC card slot for local storage
- 3-Megapixel high-definition resolution
- Vandal-proof IK08-rated housing
- Compression: H.264/MJPEG
- Power support: PoE (IEEE 802.3af)
- Free video surveillance and CMS (Central Management System) software with 64-channel license

www.level1.com Page 1 of 4

# **Specifications**

## **System Specifications**

#### Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet

IEEE 802.3u 100-BASE-TX, Fast Ethernet

IEEE 802.3af Power over Ethernet (PoE)

IEEE 802.1X Network Access Control

TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour

#### Image Sensor:

3-Megapixel 1/3.2" Progressive Scan CMOS

#### Connectors and Cabling:

1 x RJ-45 10/100 Mbps PoE port

1 x MicroSDHC/ MicroSDXC card slot

#### Button/Knob:

Reset Button

#### Indicator:

Power

#### Lens:

Fixed focal, Fixed iris, Fixed focus, f2.93mm, F2.0

#### Shutter Time:

 $1/5 \sim 1/10,000 sec$ 

#### Angle of View:

83.3°

#### Pan/Tilt/Zoom:

Digital Zoom to very high detail available on Software

## Video Compression:

H.264 / MJPEG

#### Resolution:

3M(2048 x 1536)

#### Video Format:

**RAW** 

## Power Input:

802.3af PoE

#### Power Consumption:

PoE Class 1 (IEEE802.3af) / 2.91W

## **Features**

#### General:

Backup: MicroSDHC /MicroSDXC card slot for local storage

#### Video:

Image Setting: - Adjustable image size, quality and bit rate

- Configurable brightness, sharpness, contrast, saturation, white balance and exposure
- AGC/AWB/AES
- Back Light Compensation (BLC)
- 2D Noise Reduction (2DNR)

Streaming: Up to 2 video streams

www.level1.com Page 2 of 4

## Performance

#### Data Transfer Rate:

10/100Mbps

#### Storage Capacity:

SD/MicroSD memory card of up to 64GB

#### Frame Rate:

15 fps at 2048 x 1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 720; 30 fps at 640 x 480; 15 fps at 320 x 240

# Minimum illumination:

Color: 0.1 lux at F2.0

## Environment

## Temperature (°C):

Operating: -10°C ~ 50°C

# Humidity (Non-condensing):

Operating: 10% ~ 85%

## Deployment:

Wall/Ceiling Mount

## Physical Specifications

## Dimensions (W x D x H mm):

110 x 58 x 110

## Weight (g):

202 g

## **Approval and Compliance**

#### EMI/EMS:

CE, RoHS, FCC, IK08

#### **Environmental Test:**

Vandal Resistant IK08-reted


## Others

## Operation Systems:

Microsoft Windows 8/7/Vista/XP

www.level1.com Page 3 of 4

# **Diagram**



# **Order Information**

FCS-3054

# **Package Contents**

FCS-3054 Mounting Kit Screw Kit Quick Installation Guide Resource CD (User Manual, Utility, QIG)

No liability or responsibility for any errors or omissions in the content. Specifications are subject to change without notice.

All mentioned brand names are registered trademarks and property of their owners. Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.

www.level1.com Page 4 of 4