# **FX-89011**

#### DATASHEET / BROCHURE





Nine-pin dot matrix printer offering faster printing, outstanding reliability and extremely low TCO.

The FX-890II is a high-volume, low TCO 80-column dot matrix printer designed for fast, reliable printing. A contemporary new design and small footprint make upgrading easy and add a range of new features for unprecedented flexibility.

# Market-leading print speeds1

The FX-890II offers an improved USD (ultra speed draft) speed of 735 characters per second at 12 characters per inch, making a real difference to high-volume print runs such as stock reports and large batches of invoices or freight documents.

### Outstanding reliability

Epson's dot matrix technology is already mature and very reliable, and these new printers improve the mean time between failure by 25% to 25,000 power-on hours, ideal for challenging conditions or where regular maintenance is not practical.

## Modern design

Epson's new range of dot matrix printers have a refreshingly modern design to fit in with your working environment.

### **KEY FEATURES**

- Market-leading print speeds
   Complete high-volume print runs even faster
- Very low TCO
   Cheap, long-lasting consumables and low power use
- Even better reliability
   Improved by 25% to 25,000 power-on hours
- Modern design
   Fits with your working environment
- Energy Star compliant
   To ensure the best possible energy efficiency



### PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method Impact dot matrix
Number of Pins 9 pins
Number of columns 80 columns
Pins 18 Needles (2 x 9)

PRINT

Printing Speed HighSpeed-Draft: 10 cpi: 612 chars/s, Draft: 10 cpi: 463 chars/s, NLQ: 10 cpi: 115 chars/s,

Ultra Speed-Draft: 12 cpi: 73 chars/s

Barcodes Coda bar (NW-7), Code 128, Code 39, Industrial 2 of 5, Matrix 2 of 5, POSTNET, UPC-A, UPC-E

Carbon Copies 6 plus one original

Character Sets 42

Character Tables PCAPTEC, PC437, PC720, PC850, PC858, ISO-8859-15, Roman 8, Italic

Printing Resolution 240 x 144 DPI

CONNECTIVITY

Interfaces USB - compatible with USB 2.0 specification, Bidirectional parallel

PAPER / MEDIA HANDLING

Document Feed Single sheet front and rear, Continuous media front and rear, Paper output rear

Paper Formats Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Envelopes,

Cardboard

Paper Thickness Continuous 0,46 mm

Paper

Paper Thickness Label Base 0,46 mm

Sheet

Paper Thickness Multi Part 0,12 mm - 0,46 mm
Paper Thickness Single Sheet 0,06 mm - 0,14 mm

**GENERAL** 

Power consumption 54 Watt, 0,5 Watt (economy), 8 Watt (standby)

Supply Voltage AC 198 V - 264 V

Product dimensions 414 x 375 x 177 mm (Width x Depth x Height)

Product weight 7,2 kg

Supported Temperature Operation 5° C - 35° C, Storage -30° C - 60° C
Supported Humidity Operation 10% - 80%, Storage 30% - 60%

Mean Time Between Failures 25.000 hours

Print Head Life 400 Million Strokes/Wire

Fonts Bitmap font EPSON Draft (10 CPI, 12 CPI, 15 CPI), Bitmap font EPSON OCR-B (10 CPI), Bitmap

font EPSON Roman (10 CPI, 12 CPI, 15 CPI, Proportional), Bitmap font EPSON Sans Serif (10

CPI, 12 CPI, 15 CPI, Proportional)

Noise Level Operation (Roll):55 dB (A)
Ribbon Yield 7500000 characters Black Draft

OTHER FEATURES

Emulations ESC/P, IBM PPDS

Input Data Buffer 128 kB

OTHER

Warranty 12 months Carry in

Optional warranty extension available

#### FX-890II

## WHAT'S IN THE BOX

- Driver and utilities
- User guide
- AC cable
- Ribbon



### **SUPPLIES**

• Epson SIDM Black Ribbon Cartridge for FX-890, FX-890A (C13S015329)

FX-890II

C13S015329

## **OPTIONAL ACCESSORIES**

- Pull Tractor Unit C12C933761
- Epson SIDM Paper Roll Holder for LX-300+II/1170II, FX-890/A, FX-2190, LQ-690/300+II series C12C811141
- Epson SIDM Single Sheet Feeder 150 sheets for LQ-590, FX-890/A C12C806382
- Epson SIDM Single Sheet Feeder 50 sheets for FX-890/A, LX/LQ-300+II, LQ-590 C12C806372

### LOGISTICS INFORMATION

SKU	C11CF37401
EAN code	8715946634487
Country of Origin	Indonesia
Layer	2 Units

Epson Deutschland GmbH Schiessstraße 49 D-40549 Düsseldorf Info-Line: 02159 92 79 500 Telefax: +49 (0) 211 54229-001 www.epson.de Epson in Österreich Info-Line: 01 253 49 78 333 www.epson.at Epson in der Schweiz Info-Line: 022 592 7923 www.epson.ch

1. Speeds compared with published specifications for directly competing products, May 2017.

