Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	FRISCH-Licht GmbH & Co. KG
--------------------------------	----------------------------

Supplier's address: Technik, Schlachthofweg 2, 59755 Arnsberg, DE

Model identifier: LED-WNL-O-003

trol gear, light-

control

ing

T	- 6	10 - 1- 1		
IVna	α T	IIσnt	source:	,
IVDC	vı	HEILL	Jourte.	

Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		verdrahtet		
(or other electric interface)				
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance light source:		No		
Anti-glare shield:		No	Dimmable:	No
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	parameters:	
0,	nption in on- 00 h), rounded st integer	21	Energy efficiency class	D
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		3 432 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 200
On-mode power (P _{on}), ex- pressed in W		22,7	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen-	Height	14	Spectral power dis-	See image
sions without	Width	1 134	tribution in the	in last page
separate con-	Depth	1	range 250 nm to 800	

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,380		
		nates (x and y)	0,380		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	3	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

