



HP ISO 24711 Ink Yield Test Report

Declaration of yield:

Ink Cartridge Yield:

Average K Cartridge Yield 2000 standard pages

Average Continuous Composite CMY Cartridge Yield 1600 standard pages

Values obtained by continuous printing.

Declared yield value in accordance with ISO/IEC 24711

90% Lower Confidence

K Cartridge yield	2108 pages
Continuous Composite CMY Cartridge yield	1599 pages

Date Tested: 09/17/2018 - 09/21/2018

For Questions Concerning Testing Contact:

Name: Rachel P. Q. Lim

Address: 1A Depot Close, Singapore 109842

Printer Model Used	HP OJ Pro 8720 (PP)
K Cartridge Model	F6U19A(HP952XL)
C Cartridge Model	L0S61A(HP952XL)
M Cartridge Model	L0S64A(HP952XL)
Y Cartridge Model	L0S67A(HP952XL)
Number of Cartridges Used in Testing	K=9, C=9, M=9, Y=9
Number of Cartridges Used in Calculations	K=9, C=9, M=9, Y=9
Type of Cartridges	C = Separate, M = Separate, Y = Separate, K = Separate
Supplemental Cartridges	No
Print Mode	Continuous
Number of Printers Used in Testing	3
Media Used	HP All in One 22lb Copy Paper
Paper Size	Letter size 8.5" x 11"
Paper Feed Orientation	Short Edge Feed
Computer Model	HPCompaq Elite 8300 SFF

This report applies to HP ink cartridges compatible with multiple printer models that share an identical print system. Approximate average yield is based on ISO/IEC 24711 or HP testing methodology and continuous printing. The presence of a scanner does not affect ISO/IEC 24711 test process or results.

This report applies to ink cartridges of same page yield: HP 953XL, 954XL, 955XL

CPU	Intel Core i5-3570
Memory Size	8.0 GB
Interface	USB2.0
Driver Version	38.1.1881-OJ8720
Operating System	Window 7 Professional
Application Software	Adobe Reader V6.0.1
Test Suite Version	ISO-IEC 2471202006
Power (off/on) everyday?	No
Other	Use of pre-generated print files in testing

Cartridge Testing Data:

Printer #1	HP / CN72MF61FN					
	Cartridge No.	Temperature (°C)			Cartridge Yield	Cartridge Used in Calculation
		Avg	Max	Min		
Set 1	L0S61A(HP952XL) C	22.11	22.48	21.71	1615	Yes
	F6U19A(HP952XL) K	22.10	22.48	21.71	2120	Yes
	L0S64A(HP952XL) M	22.11	22.48	21.71	1615	Yes
	L0S67A(HP952XL) Y	22.11	22.48	21.71	1615	Yes
Set 2	L0S61A(HP952XL) C	22.06	22.09	21.71	1570	Yes
	F6U19A(HP952XL) K	22.07	22.09	21.71	2125	Yes
	L0S64A(HP952XL) M	22.06	22.09	21.71	1570	Yes
	L0S67A(HP952XL) Y	22.06	22.09	21.71	1570	Yes
Set 3	L0S61A(HP952XL) C	22.08	22.09	21.71	1545	Yes
	F6U19A(HP952XL) K	22.03	22.09	21.71	2080	Yes
	L0S64A(HP952XL) M	22.08	22.09	21.71	1545	Yes
	L0S67A(HP952XL) Y	22.08	22.09	21.71	1545	Yes

Printer #2	HP / CN72MF61FS					
	Cartridge No.	Temperature (°C)			Cartridge Yield	Cartridge Used in Calculation
		Avg	Max	Min		
Set 1	L0S61A(HP952XL) C	22.10	22.48	21.71	1760	Yes
	F6U19A(HP952XL) K	22.10	22.48	21.71	2090	Yes
	L0S64A(HP952XL) M	22.10	22.48	21.71	1760	Yes
	L0S67A(HP952XL) Y	22.10	22.48	21.71	1760	Yes
Set 2	L0S61A(HP952XL) C	22.08	22.09	21.71	1755	Yes
	F6U19A(HP952XL) K	22.08	22.09	21.71	2135	Yes
	L0S64A(HP952XL) M	22.08	22.09	21.71	1755	Yes
	L0S67A(HP952XL) Y	22.08	22.09	21.71	1755	Yes
Set 3	L0S61A(HP952XL) C	22.07	22.09	21.71	1605	Yes
	F6U19A(HP952XL) K	22.03	22.09	21.71	2135	Yes

This report applies to HP ink cartridges compatible with multiple printer models that share an identical print system. Approximate average yield is based on ISO/IEC 24711 or HP testing methodology and continuous printing. The presence of a scanner does not affect ISO/IEC 24711 test process or results.

This report applies to ink cartridges of same page yield: HP 953XL,954XL, 955XL

	L0S64A(HP952XL) M	22.07	22.09	21.71	1605	Yes
	L0S67A(HP952XL) Y	22.07	22.09	21.71	1605	Yes

Printer #3		HP / CN72MF61FW				
	Cartridge No.	Temperature (°C)			Cartridge Yield	Cartridge Used in Calculation
		Avg	Max	Min		
Set 1	L0S61A(HP952XL) C	22.10	22.48	21.71	1715	Yes
	F6U19A(HP952XL) K	22.10	22.48	21.71	2125	Yes
	L0S64A(HP952XL) M	22.10	22.48	21.71	1715	Yes
	L0S67A(HP952XL) Y	22.10	22.48	21.71	1715	Yes
Set 2	L0S61A(HP952XL) C	22.06	22.09	21.71	1630	Yes
	F6U19A(HP952XL) K	22.07	22.09	21.71	2145	Yes
	L0S64A(HP952XL) M	22.06	22.09	21.71	1630	Yes
	L0S67A(HP952XL) Y	22.06	22.09	21.71	1630	Yes
Set 3	L0S61A(HP952XL) C	22.07	22.09	21.71	1630	Yes
	F6U19A(HP952XL) K	22.03	22.09	21.71	2140	Yes
	L0S64A(HP952XL) M	22.07	22.09	21.71	1630	Yes
	L0S67A(HP952XL) Y	22.07	22.09	21.71	1630	Yes

Summary

Printer #1				
Cartridge No.	K	C	M	Y
1	2120	1615	1615	1615
2	2125	1570	1570	1570
3	2080	1545	1545	1545

Printer #2				
Cartridge No.	K	C	M	Y
1	2090	1760	1760	1760
2	2135	1755	1755	1755
3	2135	1605	1605	1605

Printer #3				
Cartridge No.	K	C	M	Y
1	2125	1715	1715	1715
2	2145	1630	1630	1630

This report applies to HP ink cartridges compatible with multiple printer models that share an identical print system. Approximate average yield is based on ISO/IEC 24711 or HP testing methodology and continuous printing. The presence of a scanner does not affect ISO/IEC 24711 test process or results.

This report applies to ink cartridges of same page yield: HP 953XL, 954XL, 955XL

3	2140	1630	1630	1630
---	------	------	------	------

Type	K	C	M	Y
Total	19095	14825	14825	14825
Avg	2122	1647	1647	1647
St Dev.	22	78	78	78
90%LCB	2108	1599	1599	1599

This report applies to HP ink cartridges compatible with multiple printer models that share an identical print system. Approximate average yield is based on ISO/IEC 24711 or HP testing methodology and continuous printing. The presence of a scanner does not affect ISO/IEC 24711 test process or results.

This report applies to ink cartridges of same page yield: HP 953XL, 954XL, 955XL