Product Safety Information

WSM suspended parking, 1-sided, for tyres up to W 65 mm, D 350 x H 350 mm, anti-theft protection, steel, various number of suspension points

Manufacturer/Responsible Person: WSM Walter Solbach Metallbau GmbH, Industriestraße 20, 51545

Waldbröl, Deutschland **E-Mail:** info.de@wsm.eu

Please note the technical data of the products!

Article Numbers: 39094, 39093, 39092, 39090

Safety Instructions:

- Risk of suffocation due to improper assembly or handling of the suspended parker. Take care when assembling small parts.
- Risk of falling and risk of injury in the event of incorrect assembly or use and if the suspension hooks are overloaded.
- Protect against theft by properly securing the bikes and using a suitable lock. Note the steel ring eyelets on the hooks, but theft is still possible.
- Regular inspection of the mounting connections for stability and replacement of damaged or worn parts is recommended.
- Observe mounting heights of approx. 2000 mm and distances, as well as height offset of the hooks to prevent bicycles from tipping over and falling.
- Use protective clothing during assembly to prevent injuries from sharp tools.
- Do not exceed the maximum recommended tyre width (65 mm).
- Use the plastic coating on the hooks to prevent damage to the bikes.
- Read the user manual carefully to avoid installation errors.
- Ensure that the product is suitable for the intended use.