

Product Safety Information

1-sided lean-to parking, for tyres up to W 55 mm, D 385 x H 815 mm, galvanised steel, various number of parking spaces

Manufacturer/Responsible Person: Schäfer Shop GmbH, Industriestraße 65, 57518 Betzdorf, Deutschland

E-Mail: info@schaefer-shop.de

Please note the technical data of the products!

Article Numbers: 881979, 881978, 881970

Safety Instructions:

- Before use, ensure that all screws and fastenings are securely tightened; regularly check the stability and assembly of the parts to avoid injury.
- Attach bicycles securely to the bicycle racks and use the devices provided for bicycle frames to prevent theft.
- Mount the lean-to parker on a level surface to ensure stability and safety; ensure that the lean-to parker is securely mounted in the intended position to prevent it from tipping over.
- Fittings and fasteners should be suitable for outdoor use to prevent corrosion; the construction is corrosion-resistant, but regular inspection is important.
- Avoid overloading the car parks by observing the maximum number of bicycles to prevent accidents and damage.
- Inspect the plastic coating of the leaning bracket regularly, as it can become brittle at extreme temperatures.
- Edges and surfaces are sharp; handle the product with care to avoid injury.
- Use only recommended for bicycles with a tyre width of up to 55 mm.
- Assembly should be carried out in accordance with the enclosed instructions in order to fulfil all safety standards; the assembly instructions should be followed exactly.