

Product Safety Information

Fire protection cabinet FS 1282, different versions lock, steel, signal white RAL 9003

Manufacturer/Responsible Person: Phoenix Safe Deutschland GmbH, Bahnstr. 23, 42327 Wuppertal, Deutschland

E-Mail: info@phoenixsafe.de

Please note the technical data of the products!

Article Numbers: 193806, 193803, 193800

Safety Instructions:

- Risk of suffocation due to improper use, especially if the contents are accessed unsafely.
- Risk of injury from sharp edges or heavy components during transport or handling.
- Fire hazard due to improper use or overheating of electrical components. Remove all combustible materials in the vicinity of the cabinet.
- Information about insurance cover in the event of burglary should be clearly communicated.
- The cabinet should always be properly anchored to prevent it from tipping over. Secure the cabinet with the appropriate floor mounting to prevent it from tipping over.
- Ensure that the cabinet is not installed near heat sources to avoid heat damage.
- Check the door lock regularly to ensure that it is working properly. Make sure that the cabinet is always properly closed to ensure effective fire protection. After use, regularly ensure that all locks close correctly.
- Ensure that the fire protection cabinet is installed in accordance with the installation instructions. Operate the cabinet in accordance with local fire safety regulations.
- Do not exceed the maximum permissible weight capacity of 38 kg.
- Use only for the storage of tested refractory materials and digital storage media.
- This fire protection cabinet offers up to 60 minutes of fire protection for paper documents and digital storage media, tested up to 945° C.
- Keep keys in a safe place to prevent unauthorised access.