

Product Safety Information

Upright parker, 1-sided, for tires up to W 55 mm, D 540 x H 500 mm, hot-dip galvanized steel, various number of parking spaces, assembled

Manufacturer/Responsible Person: Schäfer Shop GmbH, Industriestraße 65, 57518 Betzdorf, Deutschland

E-Mail: info@schaefer-shop.de

Please note the technical data of the products!

Article Numbers: 881663, 881662, 881661, 881660, 881659, 881658

Safety Instructions:

- Only use the product for bicycles with tyres up to 55 mm wide. Not suitable for bikes with tyres wider than 55 mm.
- Only use U-bracket parkers for the intended bicycle types to avoid damage.
- To avoid injury, avoid tipping the U-frame parker over or installing it incorrectly.
- Improper use may result in a risk of falling.
- Regularly check the condition and stability of the Upright Parker for wear and damage to prevent injuries.
- Ensure that the U-frame parker is mounted on a stable surface to prevent it from tipping or falling over. Ensure additional stability during installation to prevent wobbling.
- Risk of suffocation due to incorrect use or overloading.
- Children should only use the U-shaped parker under supervision. Note: Not suitable for children under 14 years of age due to risk of injury. Keep out of the reach of children.
- Risk of injury from sharp edges or protruding parts of the steel frame. Take care during installation to avoid injury.
- Protect U-frame parkers from extreme weather conditions to prevent corrosion.
- Do not overload: Do not exceed the maximum number of bikes to avoid structural damage.
- Follow the assembly instructions to guarantee stability and safety.
- Procure fixing material separately for secure installation; the use of suitable fixing material is recommended.