

Product Safety Information

Pallet truck, lifter, PU/PU, without Quick-Lift, tandem

Manufacturer/Responsible Person: Toyota Material Handling Deutschland GmbH, Hannoversche Straße 113, 30916 Isernhagen, Deutschland
E-Mail: info@de.toyota-industries.eu

Please note the technical data of the products!

Article Numbers: 77321, 77295, 77294

Safety Instructions:

- Do not overload the product, observe the maximum load capacity of 2000 kg.
- Ensure that operators are properly trained to prevent injuries.
- Only use the product in accordance with the instructions and for the intended purpose.
- Drive carefully on uneven ground to avoid falling or tipping over.
- Wear suitable personal protective equipment (PPE) when using the product.
- Pay careful attention to the labelling and operating instructions.
- Use the specified grease nipples regularly for maintenance and lubrication.
- Carry out regular maintenance of the grease nipples to maximise the service life of the product.
- Do not leave the fork unattended when lowered.
- Keep the pallet truck away from edges and precipices to prevent falls and injuries.
- The product must be checked regularly for wearing parts to ensure safe operation.
- Do not overload the product beyond the maximum permissible load capacity of 2300 kg.
- Take care when using overloads that exceed the rated force of 2300 kg, as this can lead to damage or accidents.