

Product Safety Information

Folding floor container FB 1500 with rubber suspension

Please note the technical data of the products!

Article Numbers: 76070, 76061, 76060, 76059, 76058, 76057

Safety Instructions:

- Caution: Heavy product, risk of injury if handled incorrectly. Risk of injury due to the heavy weight of the container (202 kg to 221 kg).
- Ensure that the bottom flap is correctly unlocked to prevent falling parts and to avoid the risk of injury due to unintentional closing. Never empty the bottom flap while the engine is running or without adequate securing.
- Use suitable lifting and transport equipment such as a forklift or crane to move the product safely. Observe safety precautions when transporting with a forklift truck or crane. When using a forklift truck or crane, please ensure that the maximum load capacity of 1500 kg is not exceeded. When transporting with a pallet truck, ensure that the fork length is at least 1100 mm.
- Caution: Possibility of slipping during transport, observe the safety device to prevent unintentional slipping. Before stacking, ensure that the containers are secure and stable to prevent them from tipping over. Take safety precautions to minimise the risk of accidents when handling the hinged floor container.
- Read the instructions for use and safety instructions carefully before use. Include instructions for safe use and maintenance.
- Risk of suffocation due to unintentional positioning of the bottom flap. Risk of suffocation due to improper handling of the bottom flap.
- Risk of crushing if the hinged floor container is handled incorrectly. Take care when lifting heavy loads to avoid back injuries.
- Do not exceed the maximum load capacity of 1500 kg to avoid structural damage or injury. Provide safety instructions for handling with forklift trucks and cranes.
- Only allow authorised personnel to access the bottom flap. Before emptying, check that there are no persons in the danger zone.
- Provide information on correct storage methods to avoid accidents when stacking. Take care when using the rubber suspension to avoid injury when closing the bottom flap.
- Wear suitable personal protective equipment (PPE) such as a safety helmet and gloves for transport and handling.
- Close the bottom flap securely before emptying. Before emptying, check that there are no people in the danger zone.
- Carry out regular maintenance and inspection for damage to ensure safety and functionality. Label the product with manufacturer information so that it is easy to read.