

Product Safety Information

Aluminium stepladder, mobile

Manufacturer/Responsible Person: Krause-Werk GmbH & Co. KG, Am Kreuzweg 3, 36304 Alsfeld, Deutschland

E-Mail: info@krause-systems.de

Please note the technical data of the products!

Article Numbers: 95456, 95455, 95454, 95453, 95452, 95451

Safety Instructions:

- Ensure that the ladder is standing on a stable and level surface and is properly locked before using it.
- Do not use the ladder in wet or slippery conditions, in windy conditions or on unstable ground to prevent it from tipping over.
- The ladder must not be moved without suitable protection and should be protected against abrupt movements and impacts.
- Use the integrated safety harnesses in accordance with the instructions from a working height of 3400 mm to avoid the risk of falling or slipping.
- Regularly check the safety mechanisms such as pressure locks to prevent unintentional folding and fixed castors to prevent unintentional movement.
- Pay attention to the maximum load capacity of the ladder and do not apply an excessive load.
- Choking hazard due to small parts: Keep them away from children and use the stepladder properly.
- Ensure that the fixed castors are correctly fitted and locked. Use the four large fixed castors when moving the ladder.
- The maximum working height of 3400 mm must not be exceeded.
- Make sure that the steps have a maximum depth of 80 mm and are not damaged.
- The ladder can only be climbed on one side.