

Product Safety Information

Sliding door cabinet, acoustic front, W 1350 mm, 6 OH

Manufacturer/Responsible Person: Werner Works Vertriebs GmbH, Königsberger Straße 7-11, 32339 Espelkamp, Deutschland
E-Mail: info@werner-works.de

Please note the technical data of the products!

Article Numbers: 192383, 192382, 192381, 192380, 192379, 192378

Safety Instructions:

- Ensure that the product meets the technical safety requirements.
- Provide correct instructions for safe use of the product.
- Observe the maximum load per shelf to avoid structural damage.
- Take care when opening and closing the sliding doors to avoid crushing injuries.
- Regularly check the stability and integrity of the cabinet.
- The product is not suitable as a toy for children - choking hazard due to moving parts.
- In the event of damage or irregularities, stop using the product and inform the manufacturer.
- Observe the mountable parts and the weight of the door to avoid crushing injuries.
- Keep children away from the product while it is being installed or serviced.
- Do not store heavy objects on doors or door leaves to avoid the risk of collapse.
- Set up and use the product in accordance with the manufacturer's instructions.
- Carry out a safety check before commissioning the sliding doors.
- Do not use the product in a damp environment to avoid damage.
- Use suitable tools and aids for assembly.
- Anchor the rear panel correctly and securely in the carcass.
- Make sure that the cabinet is placed on a level surface to avoid wobbling and injuries.
- Avoid improper installation, as this can lead to malfunctions or hazards.
- Adjust the levelling feet correctly to compensate for unevenness and avoid the risk of falling.
- Do not use harsh or abrasive cleaning agents when cleaning the door fronts.
- Guide sliding doors in the cabinet safely and invisibly to prevent injuries.
- Use the integrated push cylinder locks to secure the doors to prevent unauthorised access.
- Back panel grooved and glued on all sides to ensure stability.
- Beware of sharp edges if melamine resin-coated chipboard is handled incorrectly.