

Product Safety Information

Extension gantry with extension arm, extension table SPEZIAL Workbench system UNIVERSAL/PROFI

Manufacturer/Responsible Person: Krieg Industriegeräte GmbH & Co. KG, Jakob-Hornung-Straße 3-5,
71296 Heimsheim, Deutschland
E-Mail: verkauf@krieg-online.de

Please note the technical data of the products!

Article Numbers: 401458, 401457, 401456, 401455, 401454, 401453, 401452, 401451, 401450, 401448,
401447, 401446, 401445, 401444, 401443, 401442, 401441, 401440, 401438, 401437, 401436, 401435,
401434, 401433, 401432, 401431, 401430, 401428, 401427, 401426, 401425, 401424, 401423, 401422,
401421, 401420

Safety Instructions:

- Observe maximum load: 120 kg for the entire gantry, 40 kg for the stabiliser.
- Ensure that the assembly gantry is securely fastened to the worktable/workbench to ensure stability.
- Install and use in accordance with the manufacturer's instructions and safety regulations.
- The product is not suitable for use by children; keep out of the reach of children.
- Regularly check for stability, fastenings and damage to minimise safety risks.
- Ensure that all parts required for assembly are complete and undamaged.
- Suitable for use with tools, equipment and workplace lighting while maintaining safety distances.
- Only use the product over stable workbenches/attachments with the intended depth.
- Do not load beyond the maximum load limits to avoid tipping or structural damage.
- Before use, ensure that all fastenings are secure and that the assembly instructions have been followed.
- When using the appliance, ensure that the work surface is kept clear of obstacles to avoid the risk of falling.
- Use only by adults who are familiar with the assembly.
- Take suitable protective measures to avoid falling objects.
- Avoid improper use or modifications to the structure.
- Use suitable personal protective equipment when assembling and using tools.
- Protect the product from moisture and extreme temperatures to prevent damage.
- Product is intended for commercial use only.
- Adjust heights and positions in 30 mm increments to ensure stability.