

# Product Safety Information

## Monitor arm Novus CLU I C, for 1 monitor up to 7 kg, with table mounting, tilt/swivel/height adjustable, various colours

**Manufacturer/Responsible Person:** Schneider-Novus Vertriebs GmbH, Holzhofring 20, 82362 Weilheim, Deutschland

**E-Mail:** info@snv.de

Please note the technical data of the products!

**Article Numbers:** 177802, 177801, 177800

### Safety Instructions:

- Only use for screens weighing 2-7 kg. Do not exceed the maximum load limit of 7 kg to prevent structural damage. Ensure that the weight of the monitor does not exceed 7 kg to ensure the stability of the arm.
- The table top thickness must be between 10-50 mm.
- Follow the installation instructions carefully to ensure stability and safety. Read the user manual carefully to understand the correct use and settings. The monitor arm should be installed and used in accordance with the instructions provided to avoid injury or damage.
- Take finger protection measures to prevent crushing injuries when adjusting the arm. Ensure that all moving parts are properly secured to prevent injury from crushing.
- Cables should be laid securely to avoid tripping hazards. Design cable management in such a way that tripping hazards are avoided, especially in private and commercial applications.
- Ensure that the table is sufficiently stable, especially under maximum load. Ensure that the monitor arm is securely mounted and fastened to the tabletop to avoid the risk of tipping or falling. Ensure that the attachment to the tabletop is securely installed to minimise the risk of the monitor falling over.
- Do not load beyond the maximum load capacity.
- Check that a correct VESA mount (75 x 75 mm or 100 x 100 mm) is used to ensure that the monitor is held securely.
- Regularly check all fastenings and parts for wear or damage to ensure safety.
- Avoid sitting or standing on the table to prevent the monitor from falling.
- Keep the workplace clean and free of obstacles to prevent accidents caused by falling.