

Product Safety Information

Material container MC 1600, with wooden floor

Manufacturer/Responsible Person: Saebu Morsbach GmbH, Zum Systembau 1, 51597 Morsbach-Schlechtingen, Deutschland
E-Mail: info@saebu.de

Please note the technical data of the products!

Article Numbers: 39075, 39074, 39073

Safety Instructions:

- The container is unloaded on site by the customer using suitable unloading equipment such as a forklift truck or crane. Take care when handling heavy materials and equipment during unloading. Use a suitable unloading device such as a forklift or crane.
- Maximum standing load of the wooden floor is 500 kg/m² with distributed load. Do not exceed the maximum standing load of 500 kg/m².
- Safety lock with handle set ensures additional protection. Check the safety lock of the door before use to prevent unintentional opening.
- GS mark shows that the container fulfils safety standards.
- The fleece coating should be used on the underside of the roof to bind water, but not in conjunction with continuous rooflights.
- Improper use can result in a risk of damaged structures. Improper use may result in injury. Ensure that all users are informed.
- Product is not suitable for use by children.
- The product should only be installed on flat and firm surfaces to prevent it from tipping or falling over. The product must be mounted on firm, level surfaces to ensure stability.
- Attach safety information and instructions in accordance with the applicable regulations.
- Check the condition of the wooden floor regularly to prevent damage and instability.
- Observe the stability and safety regulations for assembled versions.