

Product Safety Information

Safety cabinet type 90 asecos Q-CLASSIC-90, hinged doors, W 1193 x D 615 x H 1953 mm

Manufacturer/Responsible Person: asecos GmbH, Weiherfeldsiedlung 16-18, 63584 Gründau, Deutschland

E-Mail: info@asecos.com

Please note the technical data of the products!

Article Numbers: 461711, 461710, 461709, 461708, 461707, 461706, 461705

Safety Instructions:

- The cabinet can only be used indoors and is not suitable for outdoor use.
- Fire-resistant according to F90 classification. Pay attention to the fire protection regulations and corresponding safety measures in the event of fire.
- Take care when storing and handling toxic, aggressive chemicals and flammable liquids. Ensure that they are stored safely and in compliance with the law.
- The integrated ventilation system must be used correctly and checked regularly to avoid the risk of explosion from hazardous vapours.
- For safe storage, a floor drip tray must be used to prevent leaks.
- The maximum load capacity of the shelves is 75 kg; avoid overloading to ensure the stability and safety of the cupboard.
- Cabinet doors must always be properly closed to ensure unauthorised access and isolation of hazardous substances.
- Regular maintenance of the profile cylinder lock and inspection of the cabinet are required to maintain security.
- Use suitable locking mechanisms to prevent unauthorised access.
- The cabinet must be installed flat on level ground and in well-ventilated areas to prevent it from tipping over.
- All users must be trained in handling the stored hazardous substances and wear suitable personal protective equipment.
- Follow the ventilation instructions to ensure optimum air exchange.
- The cabinet should only be used by trained personnel who are familiar with the safety requirements.
- Hazardous substances must be stored in accordance with the applicable regulations and all emergency exits and escape routes must be kept clear in the event of fire.