

Product Safety Information

**dirt-trapping mat miltex Eazycare Style, angular, antistatic,
UV-resistant, washable, high twist nylon & Niltril rubber, 800 x 1200
mm, various colours**

Manufacturer/Responsible Person: Miltex GmbH, Ohmstraße 2, 68519 Viernheim, Deutschland
E-Mail: info@miltex.de

Please note the technical data of the products!

Article Numbers: 157950, 157949, 157948, 157947, 157946, 157945, 157944, 157943, 157942, 157941, 157940, 157939, 157938, 157937, 157936, 157935, 157934, 157933, 157932, 157931, 157930, 157929, 157928

Safety Instructions:

- Only use the mat on a non-slip surface to avoid the risk of slipping.
- Not suitable for use in fire risk zones or near open flames as there is a risk of fire.
- Check the mat regularly for dirt and damage and do not use if there is visible damage.
- Be aware of the risk of slipping in wet conditions and do not use the mat in heavy rain or on wet surfaces.
- Suitable for indoor and protected outdoor areas, do not use in extreme weather conditions.
- Avoid use on damp or oily surfaces or in very humid environments to minimise the risk of slipping.
- Do not use the mat as a substitute for personal protective equipment.
- Not suitable for children and keep out of reach of children to avoid misuse and choking hazard.
- Check chemical resistance if contact with strong chemicals must be avoided.
- Use only gentle cleaning agents in accordance with the washing and drying instructions: max. 70°C in washing machines, max. 80°C in tumble dryers.
- Ensure supervision to avoid the risk of choking on small parts.
- Product is flame retardant according to fire class Bfl/S1, but keep away from direct heat sources.
- Observe antistatic properties, especially when used in the vicinity of electronic devices.
- Product should not be used beyond its service life of 10 years.
- Do not bring into contact with food.
- Check commercial suitability before use in the private sector.
- No use on slippery surfaces recommended, observe safety instructions for smooth floors.
- Check the product labelling before first use and after each cleaning to ensure optimum use.
- In case of heavy soiling, use industrial washing machines and observe a maximum of 200 wash cycles.
- Do not store near direct sunlight or hot heat sources to avoid material damage.