

Product Safety Information

Tipping trolley, polyethylene various Versions

Manufacturer/Responsible Person: asecos GmbH, Weiherfeldsiedlung 16-18, 63584 Gründau, Deutschland

E-Mail: info@asecos.com

Please note the technical data of the products!

Article Numbers: 463626, 463625, 463624, 463623, 463622, 463621, 463620, 463619, 463618, 463617, 463616, 463615

Safety Instructions:

- The tipping trailer is only suitable for commercial use.
- Always wear suitable personal protective equipment, especially when handling harmful or hazardous substances (e.g. gloves, safety goggles, safety shoes).
- Only use the tipping trailer on stable, level surfaces to avoid tipping and falling over.
- Ensure that the maximum load capacity is not exceeded: 150 kg for commercial items, 250 kg for specialised applications.
- Avoid overloading to prevent structural damage and injury.
- The tipping trailer should not be exposed to direct sunlight or extreme temperatures in order to avoid material damage.
- Use lockable castors so that the trolley does not slip or roll away during use.
- Carry out regular inspections of the tipping trailer and its parts (e.g. wheels, locking mechanisms) and check them for wear or damage.
- When handling the trolley on solid surfaces, observe the remaining safety distances to prevent accidents.
- The transport of hazardous substances is only permitted if special safety requirements are met. Avoid contact with hazardous substances without suitable protective measures.
- Do not use the tipping trailer to transport food or personal items.
- Before use, the tipping trailer must be checked for visible damage and a stable position to avoid risks such as tipping over.
- Use by children is prohibited.