

Product Safety Information

Tipping container, polyethylene, various versions. Versions, tipping locking device

Manufacturer/Responsible Person: asecos GmbH, Weiherfeldsiedlung 16-18, 63584 Gründau, Deutschland

E-Mail: info@asecos.com

Please note the technical data of the products!

Article Numbers: 463639, 463638, 463637, 463633, 463632, 463631, 463651, 463650, 463649, 463645, 463644, 463643

Safety Instructions:

- Warning: Only suitable for commercial use. Not authorised for private use.
- Max. Do not exceed a maximum load of 150 kg. Do not exceed the maximum load of 250 kg (specific).
- Use the tilt locking device properly to prevent unintentional tilting and to ensure stability.
- Wear personal protective equipment (e.g. gloves, safety goggles) when handling hazardous substances.
- Place the tipping container on a stable and level surface to prevent it from tipping over.
- Use the tilting device with caution to avoid injury.
- Regular maintenance and inspection for damage to ensure safety.
- Pay attention to chemical reactions of the stored substances in order to minimise risks.
- Only handle hazardous substances with suitable protective equipment and observe safety precautions.
- Only transport tipping containers with an appropriately equipped forklift truck or pallet truck.
- Contact the manufacturer in the event of problems or damage.
- When tipping, ensure that there are no persons in the danger zone.
- Avoid the risk of slipping through correct handling and ensuring stability.
- Do not use tipping containers near open flames, high temperatures or wet surfaces.
- Read and follow the operating instructions before using the container.
- Use protective measures for the safe disposal of harmful materials.
- Avoid contact with hazardous substances and inhalation of vapours.