

Product Safety Information

Aluminum folding scaffold Krause ProTec XS, 200 kg/m², braked castors, L 2000 x W 700 x H 3800-11800 mm, various sizes. variants

Manufacturer/Responsible Person: Krause-Werk GmbH & Co. KG, Am Kreuzweg 3, 36304 Alsfeld, Deutschland

E-Mail: info@krause-systems.de

Please note the technical data of the products!

Article Numbers: 402468, 402467, 402466, 402465, 402464, 402463, 402462, 402461, 402460

Safety Instructions:

- Risk of suffocation and risk of falling due to improper use, especially if the platform is not adequately secured or when the folding scaffold is folded.
- The risk of falling when working at greater heights, especially above 3.8 m or 6.8 m, requires the use of stabilisers and safety measures such as guardrail frames and the GuardMatic system.
- There is a risk of slipping on slippery or wet surfaces and when climbing or descending; use non-slip rungs and wear non-slip shoes.
- Risk of injury due to improper handling of braked castors and sharp edges; activate brakes before transport and ensure correct assembly.
- Use scaffolding on stable, level surfaces; do not use on uneven or unstable ground to avoid tipping over.
- The maximum load of 200 kg/m² must not be exceeded; check all components regularly for damage.
- Use braked castors and ensure correct assembly of all parts, including the 6-point fixation, to ensure stability.
- Observe the necessary safety measures at great heights; for working heights above 6.8 m, fit a jib.
- In extreme weather conditions or on public terrain, exercise caution and take the necessary precautions.
- Carefully read and follow the safety information and operating instructions; observe the legal requirements and standards for scaffolding.