

Product Safety Information

Aluminum mobile scaffold Stabilo series 100, 200 kg/m², TÜV-tested, braked castors, W 750 x D 2000 or 2500, various heights & colors

Manufacturer/Responsible Person: Krause-Werk GmbH & Co. KG, Am Kreuzweg 3, 36304 Alsfeld, Deutschland

E-Mail: info@krause-systems.de

Please note the technical data of the products!

Article Numbers: 402449, 402448, 402447, 402446, 402443, 402442, 402441, 402440

Safety Instructions:

- Before using the scaffolding, check for stability, proper assembly and visible damage.
- Regularly check anti-slip rungs and decking platforms for wear and use them when climbing indoors to prevent slipping.
- Only adhere to the recommended maximum load of 200 kg/m² and do not exceed it.
- Do not use the scaffolding in windy conditions or unfavourable weather conditions to avoid tipping over and falling.
- Only use on level and stable surfaces.
- Ensure that the rolling tower is properly anchored and that the castors are braked to ensure mobility and stability.
- Check the 6-point fixation and all safety mechanisms before use.
- Use only by trained personnel at great heights and wear protective equipment including helmet and safety shoes.
- Before setting up and dismantling, ensure that the decking platforms are installed correctly at 2 metre intervals to guarantee stability.
- Ensure sufficient distance from overhanging power lines.
- Activate the GuardMatic system before use to increase safety.