

Product Safety Information

Aluminum mobile scaffold tower KRAUSE Series 10, 200 kg/m², TÜV-tested, height-adjustable castors, L 2000 or 2500 x W 750 x H 3000-14400 mm, vers. Variants

Manufacturer/Responsible Person: Krause-Werk GmbH & Co. KG, Am Kreuzweg 3, 36304 Alsfeld, Deutschland

E-Mail: info@krause-systems.de

Please note the technical data of the products!

Article Numbers: 402445, 402444, 402423, 402422, 402421, 402420, 402419, 402418, 402417, 402416, 402415, 402414, 402413, 402412

Safety Instructions:

- Use only by trained personnel or under the supervision of qualified personnel.
- The maximum load is 200 kg/m². This must not be exceeded.
- Ensure that the mobile scaffold tower is standing on firm, level ground.
- Keep the scaffold safely stowed away when not in use to avoid accidents.
- Take care when moving the mobile scaffold tower so as not to jeopardise stability and safety.
- Before use, assemble and fix all components and check for stability, including 6-point fixation and height-adjustable castors.
- Use slip-resistant decking platforms and rungs and check regularly for damage.
- Wear suitable personal protective equipment, including a safety harness, when working at great heights.
- Do not use in strong wind conditions or bad weather.
- Use only in accordance with the Guard-Matic system and the manufacturer's technical information.
- Safety railings and other fall protection devices must always be installed and used.
- Keep a safe distance from electrical cables and other sources of danger.
- Do not allow several people to use the scaffolding at the same time without prior agreement.
- Store tools and materials safely to prevent falls.
- Keep children and inexperienced persons away from the scaffolding.