

Product Safety Information

Cable ties

Manufacturer/Responsible Person: neko Vertriebsges. f. Werkzeuge u. elek. -tech., Hartkopsbever 1, 42499 Hückeswagen, Deutschland

E-Mail: info@myneko.de

Please note the technical data of the products!

Article Numbers: 709280, 709278, 709277, 709276, 709275, 709274, 709273, 709271, 709270, 709269

Safety Instructions:

- Do not use the product in combination with other products without ensuring compatibility.
- Keep the product away from children due to small parts and the resulting choking hazard.
- Not suitable for children under 3 years, choking hazard due to small parts.
- Do not exceed the maximum tensile load of 230N to avoid material failure.
- If the cable tie is visibly damaged, do not use it to avoid safety risks.
- Avoid contact with electrical components without suitable insulation to prevent the risk of electric shock.
- Do not use near open flames or extreme temperatures as the material is not fireproof.
- Only use cable ties in the temperature range from -40 °C to +85 °C to ensure material integrity.
- Protect from direct sunlight, even if UV-stabilised, to ensure stability.
- Do not use cable ties above their specified load capacity to avoid failure.
- Do not use for applications that go beyond the specified uses.
- Ensure that the product is correctly and securely attached to prevent it from slipping or coming loose.
- Store the cable ties in a dry place to maintain the integrity of the material.
- If used incorrectly, there is a risk of injury from the sharp edges of the cable tie.
- Avoid excessive tensile load and sharp edges to prevent damage to the cable ties.
- Do not use cable ties for applications above 85 °C or below -40 °C, as the mechanical properties may be impaired.