

# Product Safety Information

## Hinged door cabinet, steel, with ventilation holes, 5 OH, up to 750 kg, various colours and widths

**Manufacturer/Responsible Person:** Schäfer Shop GmbH, Industriestraße 65, 57518 Betzdorf, Deutschland

**E-Mail:** info@schaefer-shop.de

Please note the technical data of the products!

**Article Numbers:** 401829, 401827, 401826, 401825, 401822, 401821, 401819, 401817, 401816, 401815, 401812, 401811, 401809, 401807, 401806, 401805, 401802, 401801, 401799, 401797, 401796, 401795, 401792, 401791

### Safety Instructions:

- Observe the maximum total load capacity: 250 kg, 300 kg, 500 kg or 750 kg depending on the cabinet model. Avoid overloading to ensure stability.
- Do not exceed the maximum load of the shelves: 50 kg, 60 kg, 100 kg or 150 kg per shelf, depending on the model.
- Place the cabinet on a stable and level surface to prevent it from tipping over.
- Store heavy objects on lower shelves and distribute them evenly to minimise the risk of tipping.
- Do not block ventilation openings to ensure adequate ventilation and humidity control.
- Secure hinged doors and cylinder lock to prevent unauthorised access and accidental opening.
- Avoid storing hazardous or damp materials to prevent mould growth and corrosion.
- Carry out regular maintenance and checks for damage to ensure safety.
- Ensure that the cabinet is properly installed before use.
- Only use the cabinet in accordance with the intended area of use and instructions for use.
- The cabinet should be placed out of the reach of children to prevent accidents.
- For heavy loads, consider additional stability by fixing to the wall.
- Ensure that the doors function properly to avoid the risk of crushing and injury.
- The cupboard must not be used as a ladder or play equipment.